
TECHNICAL SPECIFICATION OF SS (SHUTTLE STACKER) PARKING SYSTEM



TECHNICAL SPECIFICATION OF SS (SHUTTLE STACKER) PARKING SYSTEM

Туре	SS (Shuttle Stacker) Parking system			
Variants	 Left- Right Parking Front- Back Parking 			
Mode of operation	Electric Drive –Pin Type / Pallet Type Loading & Unloading			
Loading Capacity (Kgs)	Up to 3000 Kg / Bay			
Speed Details	For Lift: Up to 50 m/min For Traverse Pallets : Up to 25 m/min.			
Motors & Drives	Motors: SWE Motor with SEW Gear Box Drives: Siemens / Mitsubishi			
Sped of Motor (RPM)	1140 RPM			
Interface	PLC with SCADA & HMI Interface			
No. Levels	2 Levels to 15 Levels			
No. Entries / Exits	2 To 6. We usually recommend 20 to 26 cars / Lift			
Structural Materials	IS2062 (Mild Steel). Brand: Tata Structural / Jindal / SAIL			
Lifting Guide Rope	6x36 Construction FMC Wire Rope. Brand M/s. Usha Martin			
Lifting guide Rollers	EN9 as per BIS Standard			
Bearings	SKF / Any international Standard*			
Lift Locking Mechanism	Hydraulic Lock / Electro Mechanical Lock			
Painting	 Rust Proof Coating – 1 Coat Epoxy Coating – 1 Coat Synthetic Enamel Paint – 2 Coats 			
Client Scope				
	 3 Phase power Supply Civil Foundation to suit the car Load Firefighting system (If Req.) 			

TECHNICAL SPECIFICATION OF SS (SHUTTLE STACKER) PARKING SYSTEM

Dimensions (mm)

All Dimensions are in mm

PD = Pit Depth = 750

TPD=Total Pit Depth = 1500

PIN TYPE SS PARKING – SUV CARS					
	DESCRIPTION	OPTION-1	OPTION-2		
BL	Bay Length	5500	5500		
BW	Bay Width	2500	2500		
вн	Bay Height	2600	2600		
GFH	Ground Floor Height	3000	3000		
No. LEVELS	No. of Levels	Up To 10	Up To 10		
SL	Shuttle Length	5300	5300		
sw	Shuttle width	3200	2250		
TW	TOTAL WIDTH	8300	16500		
LH	LIFT HEIGHT	2500	2500		
LW	LIFT WIDTH		2300		
PIT SIZE (Length X Breadth)		9000 x 6000	26000 X 6000		

OPTION-1: LEFT – RIGHT PARKING, OPTION-2: FRONT – BACK PARKING

PALLET TYPE SS PARKING – SUV CARS					
20	DESCRIPTION	OPTION-1	OPTION-2		
BL	Bay Length	5500	5500		
BW	Bay Width	2500	2500		
ВН	Bay Height	2600	2100		
GFH	Ground Floor Height	3000	3000		
No. LEVELS	No. of Levels	Up To 10	Up To 10		
SL	Shuttle Length	5300	5250		
sw	Shuttle width	3200	2210		
TW	TOTAL WIDTH	8300	1500		
LH	LIFT HEIGHT	2500	2500		
LW	LIFT WIDTH		2300		
PIT SIZE (L X B)		9000 x 6000	26000 X 6000		

TECHNICAL SPECIFICATION OF SS (SHUTTLE STACKER)